

Product information

Hydraulic Lifter Additive

PI 7/08/03/2016



Description

High performance additive that damps down noise generation of contaminated and sticky hydraulic tappets. Cleans valve bores and thus ensures optimal functioning again.

Properties

- damps hydraulic tappet noise
- cleans valve bores
- improves the lubrication properties of the oil
- tested for turbochargers and catalytic converters

Technical data

| | |
|-------------------------|--------------------------------------|
| Color / appearance | hellbraun / light brown |
| Appearance / properties | viskose Flüssigkeit / viscous liquid |
| Density at 20 °C | 0,887 g/cm ³ DIN 51757 |
| Form | flüssig / liquid |
| Odor | charakteristisch / characteristic |
| Viscosity at 20 °C | 1100 mPas |

Areas of application

For all gasoline and diesel engines. Can be mixed with all commercially available motor oils

Application

One 300 ml can of Liqui Moly hydraulic tappet additive is sufficient for up to 6 liters motor oil. The product can be added at any time. After adding, run the engine until warm. For a lasting effect, Liqui Moly Hydraulic tappet additive must be added after each oil change.

Comment

Not suitable for use on motorbikes with wet clutches.



Available pack sizes

| | |
|------------------------|-------------------------|
| 300 ml Can sheet metal | 1009 D-F-NL |
| 300 ml Can sheet metal | 2770 GB-GR-I |
| 300 ml Can sheet metal | 8345 D-PL-BG |
| 300 ml Can sheet metal | 8354 D-E-P |
| 300 ml Can sheet metal | 8367 GB-ARAB-F |
| 300 ml Can sheet metal | 8382 D-H-RO |
| 300 ml Can sheet metal | 8338 DK/N-S-FIN |
| 300 ml Can sheet metal | 2783 GB-AUS |
| 300 ml Can sheet metal | 20004 GB-F-E-USA-CAN |
| 300 ml Can sheet metal | 3919 D-RUS-UA |
| 205 l Drum sheet metal | 2581 D-GB |

Our information is based on thorough research and may be considered reliable, although not legally binding.